



MP/S angles are field-adjustable to attach members intersecting at angles. MP/S angles are load rated and provide adequate thickness and fastener quantity to the field fabricated clip angles.

Materials: 18 gauge
Finish: G90 galvanizing

Installation:

- Use all specified fasteners.
- Field-adjustable from 45°-180° (flat). Bend angle only once.
- Joist must be constrained from rotation.




Typical MP/S7 installation
 (MP/S5 similar)



Typical MP/S7 skew installation
 (MP/S5 similar)

MiTek USP Stock No.	Ref. No.	Steel Gauge	Fastener Schedule		Allowable F1 Loads (Lbs.) ¹			Code Ref.
			Qty	Type ³	33 mil ²	43 mil ²	54 mil ²	
					(20ga)	(18ga)	(16ga)	
MP/S5	S/LS50	18	4	#10	310	410	480	--
MP/S7	S/LS70	18	6	#10	405	640	745	--

- 1) Allowable loads are for one part only.
- 2) Member mils (33, 43, 54) has been considered as Grade 33.
- 3) #10 screws are ITW Buildex 10-16 HWH Teks Structural Fasteners with a nominal diameter of 0.190". Self-drilling tapping screws with equivalent physical and strength properties may be used.



MP/S Top View