

Description	MiTek Stock No.	Ref. No.	Steel Gauge	H (in)	Fastener Schedule <sup>3</sup>					DF/SP Allowable Loads (Lbs.) <sup>2</sup>				S-P-F Allowable Loads (Lbs.) <sup>2</sup>							
					Supporting Member		Supported Member			Floor			Roof			Floor			Roof		
							per Hip	per Jack	Type	100%	115%	125%	160%	100%	115%	125%	160%				
					Qty	Qty	Qty														
2 x 6 right / left	HJC26	LTHJA26, THJA26, THJU26	12	5-3/8	16	16d	5	7	10d	2750	3055	3265	2345	2420	2685	2750	1905				
2 x 8 right / left	HJC28	--	12	7-1/8	20	16d	6	8	10d	3385	3385	3385	2345	2760	2760	2760	1910				
2 x 6 terminal	HHC26	LTHJA26, THJA26	12	5-7/16	20	16d	5	--	10d	3100	3505	3505	2130	2725	2800	2800	1870				
2 x 8 terminal	HHC28	--	12	7-3/16	24	16d	6	--	10d	3505	3505	3505	2410	2805	2805	2805	1930				
2 x 6 terminal	HJHC26	--	12	5-7/16	20	16d	5	2	10d	3100	3505	3505	2410	2725	2815	2815	1935				
2 x 8 terminal	HJHC28	--	12	7-3/16	24	16d	6	2	10d	3505	3505	3505	2410	2820	2820	2820	1940				
2 x 6 terminal	HTHJ26-18	--	18	5	16	16d	7	5	16d	2295	2605	2695	1790	1985	2110	2110	1225				

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Loading published for total load of hip / jack connection.

3) **NAILS:** 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long.