

MiTek Stock No. ²	Ref. No.	Steel Gauge	Dimensions (in)			Fastener Schedule ³				DF/SP Allowable Loads (Lbs.)				
						Stud		Plate		Uplift ¹ 160%	F1 160%	F2 160%	F3 160%	F4 160%
			W	H	L	Qty	Type	Qty	Type					
RSPT4	RSP4	20	1-1/2	4-1/8	--	4	8d x 1-1/2	4	8d x 1-1/2	460	255	300	--	--
SPT22	SP1	20	1-9/16	4-3/8	3-1/2	4	10d	4	10d	735	535	275	--	--
SPT24	SP2	20	1-9/16	5-5/8	3-1/2	6	10d	6	10d	1090	535	275	--	--
SPT44	--	20	3-9/16	6-3/4	6-1/2	6	16d	6	16d	1315	845	275	--	--
RSPT6	SSP	18	1-1/2	5-7/16	--	4	10d x 1-1/2	4	10d x 1-1/2	650	--	--	--	--
RSPT6-2	DSP	18	2-3/4	5-7/16	--	8	10d x 1-1/2	6	10d x 1-1/2	900	--	--	--	--
TSP	TSP	16	1-5/8	7-7/8	--	3	10d x 1-1/2	3	10d x 1-1/2	465	--	--	--	--
						9	10d x 1-1/2	6	10d x 1-1/2	830	365	190	210	235
									10d	870				

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) SPT22, SPT24, and SPT44: the nails fastened to the wide face of the stud must be driven 30° from the perpendicular on the horizontal plane.

3) **NAILS:** 8d x 1-1/2 nails are 0.131" dia. x 1-1/2" long, 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long.