HEX HEAD

MiTek PRO SERIES

EXTERIOR STRUCTURAL WOOD SCREW

FOR DECK LEDGERS, WOOD-TO-WOOD AND STEEL-TO-WOOD CONNECTIONS



HEX HEADEXTERIOR STRUCTURAL WOOD SCREW





LOAD TABLE

			Dim	ensions ((in)		DF/SP Allowable					Loads (Lbs) ^{4,5}		
								Shear (100%)				Withdrawal	Steel to	
								Steel to Wood ² Gauge			2	Capacity	Wood Withdrawal	
							Wood					(Lbs/in		
	MiTek						-to-			of thread)	Capacity (Lbs) ⁶			
Size (in)	Stock No.	Ref. No.	L	SH	T	Finish ¹	Wood ³	14	10	7	3	100%	100%	
1/4 x 1-1/2	WS15-EXT	SDS25112	1-1/2	1/4	1-1/4	EXT		230	261	259	266	164	206	
1/4 x 2	WS2-EXT	SDS25200	2	1/4	1-3/4	EXT		306	307	289	316	160	281	
1/4 x 2-1/2	WS25-EXT	SDS25212	2-1/2	1/4	2	EXT		362	352	338	369	199	398	
1/4 x 3	WS3-EXT	SDS25300	3	3/4	2	EXT	268	418	396	387	457	199	398	
1/4 x 3-1/2	WS35-EXT	SDS25312	3-1/2	3/4	2-1/2	EXT	398	451	460	454	481	208	520	
1/4 x 4-1/2	WS45-EXT	SDS25412	4-1/2	1-1/4	3	EXT	415	516	588	589	531	214	642	
1/4 x 5	WS5-EXT	SDS2500	5	1-3/4	3	EXT	415	516	588	589	531	214	642	
1/4 x 6	WS6-EXT	SDS25600	6	1-3/4	4	EXT	415	516	588	589	531	214	642	
1/4 x 8	WS8-EXT	SDS25800	8	4-3/4	3	EXT	415	516	588	589	531	214	642	

			Dimensions (in)				S-P-F Allowable Loads (Lbs) ^{4,5}							
								Shear (100%) Steel to Wood ² Gauge				Withdrawal	Steel to	
											2	Capacity	Wood	
							Wood					(Lbs/in	Withdrawal	
	MiTek						-to-			of thread)	Capacity (Lbs) ⁶			
Size (in)	Stock No.	Ref. No.	L	SH	T	Finish ¹	Wood ³	14	10	7	3	100%	100%	
1/4 x 1-1/2	WS15-EXT	SDS25112	1-1/2	1/4	1-1/4	EXT		188	211	190	217	103	129	
1/4 x 2	WS2-EXT	SDS25200	2	1/4	1-3/4	EXT		215	244	249	248	117	204	
1/4 x 2-1/2	WS25-EXT	SDS25212	2-1/2	1/4	2	EXT		256	292	286	294	141	281	
1/4 x 3	WS3-EXT	SDS25300	3	3/4	2	EXT	227	297	340	322	365	141	281	
1/4 x 3-1/2	WS35-EXT	SDS25312	3-1/2	3/4	2-1/2	EXT	311	338	380	356	370	154	385	
1/4 x 4-1/2	WS45-EXT	SDS25412	4-1/2	1-1/4	3	EXT	364	421	460	425	379	163	489	
1/4 x 5	WS5-EXT	SDS2500	5	1-3/4	3	EXT	364	421	460	425	379	163	489	
1/4 x 6	WS6-EXT	SDS25600	6	1-3/4	4	EXT	364	421	460	425	379	163	489	
1/4 x 8	WS8-EXT	SDS25800	8	4-3/4	3	EXT	364	421	460	425	379	163	489	

1) EXT = Exterior Coat

2) Allowable shear loads assume a side plate tensile strength of 45 ksi for 14 gauge and 10 gauge, 52 ksi for 7 gauge and 58 ksi for 3 gauge.

3) Shear loads for wood-to-wood connections assume a side member thickness of 1-1/2".

4) Loads are for 100% duration of load factors, and may be increased for other duration factors in accordance with the NDS.

5) Loads are for shear applications when used as described in this catalog. Please contact MiTek for applications and installations involving tension forces.

6) Withdrawal loads for steel-towood connections assume a side plate thickness of 1/4" or less.

CUSTOMER SERVICE: **1-800-328-5934 MiTek-US.com**



PACKAGING TABLE

		Retail Box		50-count	Pack	Mini Bulk (Offering	Bulk Offering	
Use	Size (in)	MiTek Stock No.	Box/Ctn Qty	MiTek Stock No.	Box/Ctn Qty	MiTek Stock No.	Box/Ctn Qty	MiTek Stock No.	Box Qty
	1/4 x 1-1/2	WS15-EXTR25	10-pack/25-ea			WS15-EXTMB	2-box/200-ea	WS15-EXTBP	1500-ea
	1/4 x 2	WS2-EXTR25	10-pack/25-ea			WS2-EXTMB	2-box/200-ea	WS2-EXTBP	1300-ea
Exterior for	1/4 x 2-1/2	WS25-EXTR25	10-pack/25-ea			WS25-EXTMB	2-box/200-ea	WS25-EXTBP	1100-ea
Deck Ledgers,	1/4 x 3	WS3-EXTR25	10-pack/25-ea	WS3-EXTR50	5-box/50-ea	WS3-EXTMB	200-ea	WS3-EXTBP	950-ea
wood-to-wood	1/4 x 3-1/2	WS35-EXTR12	10-pack/12-ea	WS35-EXTR50	5-box/50-ea	WS35-EXTMB	200-ea	WS35-EXTBP	900-ea
and metal-to-	1/4 x 4-1/2	WS45-EXTR12	10-pack/12-ea	WS45-EXTR50	5-box/50-ea	WS45-EXTMB	200-ea	WS45-EXTBP	800-ea
wood connections	1/4 x 5	WS5-EXTR12	10-pack/12-ea	WS5-EXTR50	5-box/50-ea	WS5-EXTMB	200-ea	WS5-EXTBP	600-ea
	1/4 x 6	WS6-EXTR12	10-pack/12-ea	WS6-EXTR50	5-box/50-ea	WS6-EXTMB	200-ea	WS6-EXTBP	500-ea
	1/4 x 8	WS8-EXTR12	10-pack/12-ea	WS8-EXTR50	5-box/50-ea	WS8-EXTMB	200-ea		