WASHER HEAD

MiTek PRO SERIES

EXTERIOR STRUCTURAL WOOD SCREW

FOR DECK LEDGERS AND OTHER WOOD-TO-WOOD CONNECTIONS



The MiTek® Pro Series™ Washer Head is an ideal alternative to traditional lag screws and through-bolts. It is easy to install and reduces labor on the jobsite.

- → 1/4" diameter
- → No predrilling
- Comparable to ½" lag screw
- Flat head style allows for less interference
- T30 drive eliminates cam-out
- → Nibs under head seat head flush to wood surface
- Ode Reports: IBC, FL, LA









LOAD TABLE

				Dimensions (in)			DF/SP		SPF		LVL	
					Allowable Loads (Lbs.) ^{2,4}		Allowable Loads (Lbs.) ^{2,4}		Allowable Loads (Lbs.) ^{2,4}			
							Wood-to-Wood		Wood-to-Wood		Wood-to-Wood	
	MiTek						Shear	Withdrawal ³	Shear	Withdrawal ³	Shear	Withdrawal ³
Size (in)	Stock No.	Ref. No.	L	SH	T	Finish ¹	100%	100%	100%	100%	100%	100%
1/4 x 2-7/8	WSWH278-EXT	SDW22300	2-7/8	5/8	2	EXT	268	274	227	194		
1/4 x 3-5/8	WSWH358-EXT		3-5/8	1-3/8	2	EXT	398	398	311	282	319	358
1/4 x 4-1/2	WSWH45-EXT	SDW22458	4-1/2	2-1/4	2	EXT	415	398	364	282	358	382
1/4 x 5	WSWH5-EXT	SDW22500	5	2-3/4	2	EXT	415	398	364	282	358	382
1/4 x 6	WSWH6-EXT	SDW22600	6	3-3/4	2	EXT	415	398	364	282	358	382
1/4 x 8	WSWH8-EXT	SDWS22800	8	5-3/4	2	EXT	415	398	364	282	358	382

- 1) EXT = Exterior Coat
- 2) Shear and withdrawal loads for wood-to-wood connections assume a side member thickness of 1-1/2" for DF/SP and SPF allowable loads and 1-3/4" for LVL allowable loads.
- 3) Withdrawal loads are derived from the minimum of head pull through tests and withdrawal capacity of threaded portion in main member.
- 4) Load are for 100% duration of load, and may be increased for the other duration factors in accordance the NDS.



PACKAGING TABLE

		Retail Box (offering	50-Count	Pack	Mini Bulk Offering		
Use	Size (in)	MiTek Stock No.	Box/Ctn Qty	MiTek Stock No.	Box/Ctn Qty	MiTek Stock No.	Box/Ctn Qty	
Exterior for Deck Ledgers & other wood- to-wood connections	1/4 x 2-7/8	WSWH278-EXTR25	10-pack/25-ea	WSWH278-EXTR50	5-box/50-ea	WSWH278-EXTMB	200-ea	
	1/4 x 3-5/8	WSWH358-EXTR12	10-pack/12-ea	WSWH358-EXTR50	5-box/50-ea	WSWH358-EXTMB	200-ea	
	1/4 x 4-1/2	WSWH45-EXTR12	10-pack/12-ea	WSWH45-EXTR50	5-box/50-ea	WSWH45-EXTMB	200-ea	
	1/4 x 5	WSWH5-EXTR12	10-pack/12-ea	WSWH5-EXTR50	5-box/50-ea	WSWH5-EXTMB	200-ea	
	1/4 x 6	WSWH6-EXTR12	10-pack/12-ea	WSWH6-EXTR50	5-box/50-ea	WSWH6-EXTMB	200-ea	
	1/4 x 8	WSWH8-EXTR12	10-pack/12-ea	WSWH8-EXTR50	5-box/50-ea	WSWH8-EXTMB	200-ea	

CUSTOMER SERVICE: 1-800-328-5934 | MiTek-US.com