WASHER HEAD EXT

MiTek PRO SERIES

STRUCTURAL WOOD SCREW

FOR DECK LEDGERS AND OTHER WOOD-TO-WOOD CONNECTIONS



The MiTek® ProSeries™ Washer Head is an ideal alternative to traditional lag screws and through-bolts. It is easy to install and reduces labor on the jobsite.

- → 1/4" diameter
- → No predrilling
- → Comparable to ½" lag screw
- → Flat head style allows for less interference
- Sharp cut-point reduces installation torque and splitting
- → T30 Torx drive eliminates cam-out
- → Nibs under head seat head flush to wood surface

Code Reports: ICC-ES #2761, FL 17231.1, LA City RR 25850







LOAD TABLE

| | | | Dimensions (in) | | | | DF/SP | | SPF | | LVL | |
|-------------|-------------|-----------|-----------------|-------|---|-------------------------------------|--------------------|-------------------------------------|--------------------|-------------------------------------|--------------------|-------------------------|
| | | | | | | Allowable Loads (Lbs.) ⁴ | | Allowable Loads (Lbs.) ⁴ | | Allowable Loads (Lbs.) ⁴ | | |
| | | | | | | | Woo | d to Wood | Wood to Wood | | Wood to Wood | |
| | USP | | | | | | Shear ² | Withdrawal ³ | Shear ² | Withdrawal ³ | Shear ² | Withdrawal ³ |
| Size (in) | Stock No. | Ref. No. | L | SH | T | Finish ¹ | 100% | 100% | 100% | 100% | 100% | 100% |
| 1/4 x 2-7/8 | WSWH278-EXT | SDW22300 | 2-7/8 | 5/8 | 2 | EXT | 268 | 274 | 227 | 194 | | |
| 1/4 x 3-5/8 | WSWH358-EXT | | 3-5/8 | 1-3/8 | 2 | EXT | 268 | 398 | 227 | 282 | 319 | 358 |
| 1/4 x 4-1/2 | WSWH45-EXT | SDW22458 | 4-1/2 | 2-1/4 | 2 | EXT | 415 | 398 | 364 | 282 | 358 | 382 |
| 1/4 x 5 | WSWH5-EXT | SDW22500 | 5 | 2-1/4 | 2 | EXT | 415 | 398 | 364 | 282 | 358 | 382 |
| 1/4 x 6 | WSWH6-EXT | SDW22600 | 6 | 2-1/4 | 2 | EXT | 415 | 398 | 364 | 282 | 358 | 382 |
| 1/4 x 8 | WSWH8-EXT | SDWS22800 | 8 | 2-1/4 | 2 | EXT | 415 | 398 | 364 | 282 | 358 | 382 |

- 1) EXT = Exterior Coat
- 2) Shear load for wood-to-wood connections assume a side member thickness of 1-1/2" for DF/SP and SPF allowable loads.
- 3) Withdrawal loads are derived from the minimum of head pull through tests and withdrawal capacity of threaded portion in main member.
- 4) Load are for 100% duration of load, and may be increased for the other duration factors in accordance the NDS.



PACKAGING TABLE

| | | | Retail Box | Offering | 50-count Pa | ack | Mini Bulk Offering | | |
|---------------------------|--|-------------|----------------|---------------|----------------|-------------|--------------------|-------------|--|
| Finish | Use | Size (in) | USP Stock No. | Box/Ctn Qty | USP Stock No. | Box/Ctn Qty | USP Stock No. | Box/Ctn Qty | |
| Exterior Coat (EXT) | Exterior for Deck Ledgers & other wood- to-wood connections | 1/4 x 2-7/8 | WSWH278-EXTR25 | 10-pack/25-ea | WSWH278-EXTR50 | 5-box/50-ea | WSWH278-EXTMB | 200-ea | |
| | | 1/4 x 3-5/8 | WSWH358-EXTR12 | 10-pack/12-ea | WSWH358-EXTR50 | 5-box/50-ea | WSWH358-EXTMB | 200-ea | |
| | | 1/4 x 4-1/2 | WSWH45-EXTR12 | 10-pack/12-ea | WSWH45-EXTR50 | 5-box/50-ea | WSWH45-EXTMB | 200-ea | |
| | | 1/4 x 5 | WSWH5-EXTR12 | 10-pack/12-ea | WSWH5-EXTR50 | 5-box/50-ea | WSWH5-EXTMB | 200-ea | |
| | | 1/4 x 6 | WSWH6-EXTR12 | 10-pack/12-ea | WSWH6-EXTR50 | 5-box/50-ea | WSWH6-EXTMB | 200-ea | |
| | | 1/4 x 8 | WSWH8-EXTR12 | 10-pack/12-ea | WSWH8-EXTR50 | 5-box/50-ea | WSWH8-EXTMB | 200-ea | |

CUSTOMER SERVICE: 1-800-328-5934 | MiTek-US.com