HEX HEAD structural wood screw

FOR DECK LEDGERS AND OTHER WOOD-TO-WOOD CONNECTIONS

Mitek[®] PRO SERIES

Ten)

The MiTek[®] ProSeries[™] Hex Head is ideal for numerous framing applications. It can be used in wood-to-wood and metal-to-wood applications.

- → ¼" diameter
- ∃ No predrilling
- → Comparable to ½" lag screw
- ⇒ Low profile head style can be driven flush or countersunk
- ⇒ Sharp cut-point reduces installation torque and splitting
- ∋ 3/8" hex drive
- ∃ Length identification stamps on all WS Heads



Code Reports: ICC-ES #2761, FL 17231.1, LA City RR 25850

HEX HEAD STRUCTURAL WOOD SCREW



Mitek[®] PRO Series

LOAD TABLE

			Dimensions (in)				DF/SP Allowable Loads (Lbs.) ^{2,4,5}						
								Shear	(100%	5)		Withdrawal	Steel to
								:	Steel to	Wood	5	Capacity	Wood
							Wood		Gau	ıge		(Lbs/in.	Withdrawal
	USP						to					of thread)	Capacity (Lbs.) ⁶
Size (in)	Stock No.	Ref. No.	L	SH	Т	Finish ¹	Wood ³	14	10	7	3	100%	100%
1/4 x 1-1/2	WS15-EXT	SDS25112	1-1/2	1/4	1-1/4	EXT		230	261	259	266	164	206
1/4 x 2	WS2-EXT	SDS25200	2	1/4	1-3/4	EXT		306	307	289	316	160	281
1/4 x 2-1/2	WS25-EXT	SDS25212	2-1/2	1/4	2	EXT		362	352	338	369	199	398
1/4 x 3	WS3-EXT	SDS25300	3	3/4	2	EXT	268	418	396	387	457	199	398
1/4 x 3-1/2	WS35-EXT	SDS25312	3-1/2	3/4	2-1/2	EXT	268	451	460	454	481	208	520
1/4 x 4-1/2	WS45-EXT	SDS25412	4-1/2	1-1/4	3	EXT	415	516	588	589	531	214	642
1/4 x 5	WS5-EXT	SDS2500	5	1-3/4	3	EXT	415	516	588	589	531	214	642
1/4 x 6	WS6-EXT	SDS25600	6	1-3/4	4	EXT	415	516	588	589	531	214	642
1/4 x 8	WS8-EXT	SDS25800	8	4-3/4	3	EXT	415	516	588	589	531	214	642

			Dim	ensions	(in)				S-P-	F Allov	wable L	.oads (Lbs.) ^{2,4,5}	
								Shea	r (100%	5)		Withdrawal	Steel to
									Steel to	Wood	6	Capacity	Wood
							Wood		Ga	uge		(Lbs/in.	Withdrawal
							to					of thread	Capacity (Lbs.) ⁶
Size (in)	USPStock No.	Ref. No.	L	SH	Т	Finish ¹	Wood ³	14	10	7	3	100%	100%
1/4 x 1-1/2	WS15-EXT	SDS25112	1-1/2	1/4	1-1/4	EXT		188	211	190	217	103	129
1/4 x 2	WS2-EXT	SDS25200	2	1/4	1-3/4	EXT		215	244	249	248	117	204
1/4 x 2-1/2	WS25-EXT	SDS25212	2-1/2	1/4	2	EXT		256	292	286	294	141	281
1/4 x 3	WS3-EXT	SDS25300	3	3/4	2	EXT	227	297	340	322	365	141	281
1/4 x 3-1/2	WS35-EXT	SDS25312	3-1/2	3/4	2-1/2	EXT	227	338	380	356	370	154	385
1/4 x 4-1/2	WS45-EXT	SDS25412	4-1/2	1-1/4	3	EXT	364	421	460	425	379	163	489
1/4 x 5	WS5-EXT	SDS2500	5	1-3/4	3	EXT	364	421	460	425	379	163	489
1/4 x 6	WS6-EXT	SDS25600	6	1-3/4	4	EXT	364	421	460	425	379	163	489
1/4 x 8	WS8-EXT	SDS25800	8	4-3/4	3	EXT	364	421	460	425	379	163	489

1) EXT = Exterior Coat

2) Allowable shear loads assume a side plate tensile strength of 45 ksi for 14 gauge and 10 gauge, 52 ksi for 7 gauge and 58 ksi for 3 gauge.

3) Shear loads for wood-to-wood connections assume a side member thickness of 1-1/2".

4) Loads are for 100% duration of load factors, and may be increased for other duration factors in accordance with the NDS.

5) Loads are for shear applications when used as described in this catalog. Please contact MiTek for applications and installations involving tension forces.

6) Withdrawal loads for steel-towood connections assume a side plate thickness of 1/4" or less.

CUSTOMER SERVICE: 1-800-328-5934 MiTek-US.com



PACKAGING TABLE

			Retail Box	c Offering	50-count	Pack	Mini Bulk Offering		
Finish	Use	Size (in)	USP Stock No.	Box/Ctn Qty	USP Stock No.	Box/Ctn Qty	USP Stock No.	Box/Ctn Qty	
		1/4 x 1-1/2	WS15-EXTR25	10-pack/25-ea			WS15-EXTMB	2-box/200-ea	
		1/4 x 2	WS2-EXTR25	10-pack/25-ea			WS2-EXTMB	2-box/200-ea	
	Exterior	1/4 x 2-1/2	WS25-EXTR25	10-pack/25-ea			WS25-EXTMB	2-box/200-ea	
Exterior	for Deck	1/4 x 3	WS3-EXTR25	10-pack/25-ea	WS3-EXTR50	5-box/50-ea	WS3-EXTMB	200-еа	
Coat	Ledgers & other wood-to-	1/4 x 3-1/2	WS35-EXTR12	10-pack/12-ea	WS35-EXTR50	5-box/50-ea	WS35-EXTMB	200-ea	
(EXT)	wood	1/4 x 4-1/2	WS45-EXTR12	10-pack/12-ea	WS45-EXTR50	5-box/50-ea	WS45-EXTMB	200-ea	
	connections	1/4 x 5	WS5-EXTR12	10-pack/12-ea	WS5-EXTR50	5-box/50-ea	WS5-EXTMB	200-ea	
		1/4 x 6	WS6-EXTR12	10-pack/12-ea	WS6-EXTR50	5-box/50-ea	WS6-EXTMB	200-еа	
		1/4 x 8	WS8-EXTR12	10-pack/12-ea	WS8-EXTR50	5-box/50-ea	WS8-EXTMB	200-еа	

©2018 MITEK INC, ALL RIGHTS RESERVED. #2483-HH 2/2018