

1. Product and Company Identification

Product Name: CIA-GEL 6000-GP Part A

Product Use: Rebar Dowel/Anchor Installations

Company Identification:

USP Structural Connectors, a MiTek® Company
14305 Southcross Drive, Suite 200
Burnsville, MN 55306
Contact Phone: 1.800.328.5934
(9:00a.m. – 5:00p.m. CST)

Emergency Phone:

Chem-Tel:
1.800.255.3924 (24hrs)

2. Hazards Identification

GHS Classification

Health	Physical	Environmental
Skin Sensitizer – Cat. 1B Skin Irritant – Cat. 2 Eye Irritant – Cat. 2	Not Classified	Not Classified

GHS Label:

Danger:



Causes Eye Irritation
Skin Irritant
May cause skin sensitization
Heated vapors can cause irritation



Carcinogen

Emergency Overview

Avoid contact with the skin and eyes
Avoid prolonged and/or repeated contact with skin
Wear protective clothing
Use with adequate ventilation

Primary Route of Exposure

Eyes, skin and inhalation

Carcinogenicity

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

3. Composition/ Information on Ingredients

CAS Number

25085-99-8
13463-67-7
Proprietary

Content

40 – 70%
1 – 5%
30 – 50%

Chemical Name

Diglycidyl Ether of Bisphenol A
Titanium Dioxide
Non-Hazardous Proprietary Ingredients

4. First Aid Measures

Inhalation: Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

Skin: Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

Ingestion: Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

5. Fire Fighting Measures

Flash Point: >148°C (300°F)

Flammability: Non- Flammable

Extinguisher Media

Carbon Dioxide, Dry Chemical, Water Fog

Unusual Fire and Explosion Hazard

None Known

Special Fire Fighting Procedures

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

6. Accidental Release Measures

Personal Precautions:

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

Environmental Precautions

Avoid all personal contact, scoop up with spade and place in disposable metal container.

7. Handling and Storage

Store in a cool dry place out of direct rays of the sun. Keep from freezing. Recommended storage temperatures range in between 4° and 35° C (40°F and 95° F).

8. Exposure Control and Personal Protection

Exposure Guidelines

Component	CAS#	OSHA, PEL	ACGIH, TWA
Titanium Dioxide (Total Dust)	13463-67-7	15mg/m ³	10mg/m ³

Engineering Measures: Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

Personal Protective Equipment

Respiratory Protection

None normally required. Use a NIOSH –approved organic vapor chemical cartridge Respirator when air movement is inadequate to control vapor build-up.

Eye/Face Protection

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

Skin / Body Protection

Wear Suitable gloves (neoprene, nitrile rubber or PVC).

Other Protective Clothing or Equipment

Wear appropriate apparel to prevent skin contact

9. Physical and Chemical Properties

Appearance:	White Paste
Evaporation Rate:	Non-volatile
Odor:	Slight Odor
Water Solubility:	Insoluble
Specific Gravity:	1.58 g/cc
Vapor Density:	Non-volatile
Vapor Pressure:	N/A
VOC Content:	0 g/l
pH:	N/D
Boiling Point:	N/A

10. Stability and Reactivity

Stability:	Stable
Hazardous Reactions:	Non-hazardous when stored and handled according to instructions.
Thermal Decomposition:	Stable under normal conditions.
Incompatibility:	Strong acids, peroxides and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

11. Toxicological Information

Acute Oral Toxicity:

Not Determined

Acute Dermal Toxicity:

Not Determined

Acute Inhalation Toxicity:

Not Determined

Skin Irritation:

Sensitizer/ Irritant

The product has not been tested. The statement has been derived from the properties of the individual components.

Eye Irritation:

Irritant

The product has not been tested. The statement has been derived from the properties of the individual components.

Respiratory Irritation:

Inhalation of vapors or mists may cause irritation to the respiratory system.

Sensitization:

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

Carcinogenicity Classification:

(Titanium Dioxide)

IARC Group2B: Possibly carcinogenic to humans.

12. Ecological Information**Acute Toxicity for:****Fish:**

Diglycidyl Ether of Bisphenol A:

Fathead minnow/LC50 (96hrs): >3.1 mg/l

Aquatic Invertebrates:

Diglycidyl Ether of Bisphenol A:

Water Flea Daphnis/EC 50 (48hrs): > 1.4mg/l

Algae:

No Data Available

Microorganisms:

Diglycidyl Ether of Bisphenol A:

Bacteria, (Growth inhibition)/IC50 (18hrs): > 42.6mg/l

Mobility:

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

13. Disposal Considerations

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

14. Transportation Information

Not DOT Regulated – Non Hazardous

15. Regulatory Information

HMIS Rating	
Health	*2
Flammability	1
Physical Hazard	0
PPE	B



Hazard Rating: 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

Federal Regulations

SARA Title 313
CA Prop 65
TSCA

Chronic Health Hazard
Titanium Dioxide is regulated by CA Prop 65.
Listed

State Regulations:

State RTK
NJ, MA, PA

CAS#
13463-67-7

Chemical Name
Titanium Dioxide

16. Other Information

Hazard Communication: This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, USP Structural Connectors, a MiTek® Company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.

1. Product and Company Identification

Product Name: CIA-GEL 6000-GP Part B

Product Use: Rebar Dowel/Anchor Installations

Company Identification:

USP Structural Connectors, a MiTek® Company
14305 Southcross Drive, Suite 200
Burnsville, MN 55306
Contact Phone: 1.800.328.5934
(9:00a.m. – 5:00p.m. CST)

Emergency Phone:

Chem-Tel:
1.800.255.3924 (24hrs)

2. Hazards Identification

GHS Classification

Health	Physical	Environmental
Skin Corrosion – Cat. 1 Serious Eye Damage – Cat. 1 Reproductive Tox – Cat. 2 Carcinogen – Cat. 1A	Not Classified	Toxic to Aquatic Life – Cat. 2

GHS Label:

Danger:



Corrosive to skin and eyes
Skin Irritant



Maternal toxic effects per animal testing

Emergency Overview

Causes skin burns
Causes severe eye damage
Heated vapors can cause irritation
Avoid contact with the skin and eyes
Avoid breathing fume/gas/mist/vapors/spray
Wear protective gloves/ protective clothing/ eye protection/ face protection
Use outdoors or in a well-ventilated area

Primary Route of Exposure

Eyes, skin and inhalation

Carcinogenicity

This product or one of its ingredients present at 0.1% or more is not listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

3. Composition/ Information on Ingredients

CAS Number

140-31-8
84852-15-3
Proprietary

Content

5 – 10%
10 – 20%
60 – 80%

Chemical Name

n-aminoethylpiperazine
Nonyl phenol
Non-Hazardous Proprietary Ingredients

4. First Aid Measures

Inhalation: Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

Skin: Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

Ingestion: Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

Other: Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

5. Fire Fighting Measures

Flash Point: >93°C (>200°F)

Flammability: Non- Flammable

Extinguisher Media

Carbon Dioxide, Dry Chemical, Water Fog

Unusual Fire and Explosion Hazard

None Known

Special Fire Fighting Procedures

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

6. Accidental Release Measures

Personal Precautions:

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

Environmental Precautions

Avoid all personal contact, scoop up with spade and place in disposable metal container.

7. Handling and Storage

Store in a cool dry place out of direct rays of the sun. Keep from freezing. Recommended storage temperatures range in between 4° and 35° C (40°F and 95° F).

8. Exposure Control and Personal Protection

Exposure Guidelines

Engineering Measures: Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

Personal Protective Equipment

Respiratory Protection

None normally required. Use a NIOSH –approved organic vapor chemical cartridge Respirator when air movement is inadequate to control vapor build-up.

Eye/Face Protection

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

Skin / Body Protection

Wear Suitable gloves (neoprene, nitrile rubber or PVC.)

Other Protective Clothing or Equipment

Wear appropriate apparel to prevent skin contact

9. Physical and Chemical Properties

Appearance:	Black Paste
Evaporation Rate:	Non-volatile
Odor:	Slight Amine Odor
Water Solubility:	Insoluble
Specific Gravity:	1.69 g/cc
Vapor Density	Non-volatile
Vapor Pressure:	N/A
VOC Content:	0 g/l
pH:	N/D
Boiling Point:	N/A

10. Stability and Reactivity

Stability:	Stable
Hazardous Reactions:	Non-hazardous when stored and handled according to instructions.
Thermal Decomposition:	Stable under normal conditions.
Incompatibility:	Strong acids, peroxides and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

11. Toxicological Information

Acute Oral Toxicity:

Not Determined

Acute Dermal Toxicity:

Not Determined

Acute Inhalation Toxicity:

Not Determined

Skin Irritation:

Corrosive to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

Eye Irritation:

Severe damage to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

Respiratory Irritation:

Inhalation of vapors or mists may cause irritation to the respiratory system.

Sensitization:

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

Maternal Toxicity:

Nonyl phenol causes maternal toxic effects per animal testing.

Carcinogenicity Classification:

This product or one of its ingredients present at 0.1% or more is not listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

12. Ecological Information**Acute Toxicity for:****Fish:**

Nonyl phenol:

Fathead minnow/LC50 (96hrs): 0.135mg/l

Aquatic Invertebrates:

Nonyl phenol:

Water Flea Daphnis/EC 50 (48hrs): 0.14mg/l

Algae:

Nonyl phenol:

Green Algae/EC 50 (96hrs): 0.41mg/l

Microorganisms:

No Data Available

Mobility:

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

13. Disposal Considerations

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

14. Transportation Information**Land Transport****Transportation Information DOT Shipping Information:**

CARTRIDGE – New Limited Quantity, LTD QTY

BULK – Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III

Air Transport**IATA/ICAO Shipping name:**

CARTRIDGE: Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III

BULK: Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III

Maritime Transport

IMDG Shipping name:

CARTRIDGE: Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III

BULK: Corrosive Liquids, NOS (aminoethylpiperazine, nonylphenol), Class 8, UN 1760, PG III

15. Regulatory Information

HMIS Rating	
Health	*2
Flammability	1
Physical Hazard	0
PPE	B

NFPA RATING



Hazard Rating: 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

Federal Regulations

SARA Title 313	Acute Health Hazard
CA Prop 65	Not Regulated
TSCA	Listed

State Regulations:

State RTK	CAS#	Chemical Name
NJ, MA, PA	140-31-8	n-aminoethylpiperazine

16. Other Information

Hazard Communication: This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, USP Structural Connectors, a MiTek® Company does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.