

| Joist Size | MiTek Stock No. | Ref. No. | Steel Gauge | Dimensions (in) |       |       | Fastener Schedule <sup>3</sup> |      |      |      |       |             | DF/SP                               |                     |
|------------|-----------------|----------|-------------|-----------------|-------|-------|--------------------------------|------|------|------|-------|-------------|-------------------------------------|---------------------|
|            |                 |          |             | W               | H     | D     | Header                         |      |      |      | Joist |             | Allowable Loads (Lbs.) <sup>1</sup> |                     |
|            |                 |          |             |                 |       |       | Top                            |      | Face |      | Qty   | Type        | 125%                                | Uplift <sup>2</sup> |
|            |                 |          |             |                 |       |       | Qty                            | Type | Qty  | Type |       |             |                                     |                     |
| 2 x 6      | FHD26           | PFDS26   | 18          | 1-9/16          | 5-3/8 | 1-1/2 | 2                              | 16d  | 2    | 16d  | 2     | 10d x 1-1/2 | 960                                 | 175                 |

1) Loads listed are per side.

2) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

3) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 16d nails are 0.162" dia. x 3-1/2" long.

10d x 1-1/2 nails may be substituted for 16d header nails with a maximum load of 960 lbs.