

MiTek Stock No.	Ref. No.	Ga	Dimensions (in)				Fastener Schedule ²				DF/SP Header Allowable Loads (Lbs.)				S-P-F Header Allowable Loads (Lbs.)			
			W	H	D	A	Header		Joist		100%	115%	125%	Uplift ¹	100%	115%	125%	Uplift ¹
							Qty	Type	Qty	Type								
HDQ179IF	HUCQ1.81/9-SDS	14	1-13/16	9	3	13/16	8	WS3	4	WS15	3340	3605	3605	1110	2375	2735	2970	935
HDQ17112IF	HUCQ1.81/11-SDS	14	1-13/16	11	3	13/16	10	WS3	6	WS15	3340	3340	3340	1580	2805	2805	2805	1325
HDQ1714IF	-- --	14	1-13/16	13-3/8	3	13/16	12	WS3	6	WS15	4660	4870	4955	2035	2805	2805	2805	1325
HDQ310IF	HUCQ310	14	2-9/16	9	3	1-3/16	8	WS3	4	WS15	3340	3605	3605	1110	2375	2735	2970	935
HDQ210-2IF	HUCQ210-2	14	3-1/4	9	3	1-1/2	12	WS3	6	WS3	5015	5590	5590	2975	3565	4100	4455	2500
HDQ410IF	HUCQ410-SDS	14	3-9/16	9	3	1-1/2	12	WS3	6	WS3	5015	5590	5590	2975	3565	4100	4455	2500
HDQ412IF	HUCQ412-SDS	14	3-9/16	11	3	1-1/2	14	WS3	6	WS3	5605	5605	5605	3280	4160	4695	4695	2500
HDQ210-3IF	HUCQ210-3	14	4-5/8	9	3	1-1/2	12	WS3	6	WS3	5015	5590	5590	2975	3565	4100	4455	2500
HDQ5210IF	HUCQ5.25/9-SDS	14	5-1/4	9	3	1-1/2	12	WS3	6	WS3	5015	5590	5590	2975	3565	4100	4455	2500
HDQ5212IF	HUCQ5.25/11-SDS	14	5-1/4	11	3	1-1/2	14	WS3	6	WS3	5605	5605	5605	3280	4160	4695	4695	2500
HDQ610IF	HUCQ610	14	5-1/2	9	3	1-1/2	12	WS3	6	WS3	5015	5590	5590	2975	3565	4100	4455	2500
HDQ612IF	HUCQ612	14	5-1/2	11	3	1-1/2	14	WS3	6	WS3	5605	5605	5605	3280	4160	4695	4695	2500

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) MiTek's WS3 structural wood screws are 1/4" dia. x 3" long and are included with HDQIF hangers.