

MiTek Stock No.	Ref. No.	Steel Gauge	W (in)	O.C. Dim Between Anchors (in)	Installation Type	Fastener Schedule <sup>3,5</sup>						DF/SP Allowable Loads (Lbs.) <sup>1,2</sup>	S-P-F Allowable Loads (Lbs.) <sup>1,2</sup>
						Anchor Washers		Threaded Rod		Girder			
						Qty	Type	Qty	Dia (in)	Qty	Type	Uplift 160%	Uplift 160%
HUGT2	HGT-2	7	3-5/16	5-3/4	Wood	4	LBP58-TZ	2	5/8	8	10d	9575	6925
					Concrete	--	--	2	3/4	8	10d		
HUGT3	HGT-3	7	4-15/16	7-3/8	Wood	4	LBP58-TZ	2	5/8	8	10d	9860	7805
					Concrete	--	--	2	3/4	8	10d		
HUGT4	HGT-4	7	6-7/8	9	Wood	4	LBP58-TZ	2	5/8	8	10d	9860	7790
					Concrete	--	--	2	3/4	8	10d		

1) Allowable loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Listed loads apply where roof pitch is between 3:12 and 8:12.

3) Additional anchorage products to be designed by others.

4) Designer must specify anchor bolt type, length, and holdown device.

5) **NAILS:** 10d nails are 0.148" dia. x 3" long.