

Option	Skewed <sup>1,3</sup>	Sloped Seat <sup>2</sup>	Sloped / Skewed <sup>1,2,3</sup>	Top Flange Offset		Saddle
Range	1° to 45°	1° to 45°	See Sloped Seat and Skewed	--		--
Allowable Loads	100% of table load	100% of table load	100% of table load	<b>Hanger Width</b> 3-1/2" or less 3-9/16" to 5-1/2" 5-9/16" to 7-1/2"	<b>% of table load:</b> 60% 75% 85%	100% of table load per side
Ordering	Add <i>SK</i> , angle required, right ( <i>R</i> ) or left ( <i>L</i> ), and square cut ( <i>SQ</i> ) or bevel cut ( <i>BV</i> ) to product number. Ex. HWUH410_SK45R_SQ	Add <i>SL</i> , slope required, and up ( <i>U</i> ) or down ( <i>D</i> ), to product number. Ex. HWUH410_SL30D	See Sloped Seat and Skewed. Ex. HWUH410_SK45R_SQ_SL30D	Add <i>OS</i> , and right ( <i>R</i> ) or left ( <i>L</i> ), to product number. Ex. HWUH410_OSL		Add <i>SA</i> , and saddle width required to product number. Ex. HWUH410_SA=5-1/2"

- 1) Skewed hangers with skews greater than 15° may have all joist nailing on outside flange.
- 2) Sloped or sloped / skewed hangers with slopes greater than 15° may have additional joist nails.
- 3) For skewed hangers, the required cut type (square or bevel) of joist member may vary based on skew angle and width of hanger. Some square cut hangers will require custom pricing due to welded back plate.