

Beam Width (in)	MiTek Stock No.	Ref. No.	Steel Gauge		Dimensions (in)			Fastener Schedule ⁴					Allowable Loads (Lbs.) ²			
			Top Flange	U-Strap	W	H ³	L	Header			Joist		Floor	Roof		Uplift ¹ 160%
								Top Qty	Face Qty	Type	Qty	Type	100% ³	115%	125%	
3-1/8	KGLT3	--	3	7	3-1/4	specify	10	4	6	WS3	8	WS3	10555	10965	11055	1935
	KHGLT3	HGLT3					12	6	12	WS3	6	WS3	12495	12495	12495	1935
3-1/2	KGLT4	--	3	7	3-5/8	specify	10	4	6	WS3	8	WS3	10555	10965	11055	1935
	KHGLT4	HGLT4, HGLTV4					12	6	12	WS3	6	WS3	12495	12495	12495	1935
5-1/8	KGLT5	--	3	7	5-1/4	specify	10	4	6	WS3	8	WS3	10555	10965	11055	1935
	KHGLT5	HGLT5, HGLTV5					12	6	12	WS3	6	WS3	12495	12495	12495	1935
5-5/16	KHGLT537	HGLTV5.37	3	7	5-3/8	specify	12	6	12	WS3	6	WS3	12495	12495	12495	1935
5-1/2	KGLT6	--	3	7	5-5/8	specify	12	4	6	WS3	8	WS3	10555	10965	11055	1935
	KHGLT6	HGLT6, HGLTV6					12	6	12	WS3	6	WS3	12495	12495	12495	1935
6-3/4	KGLT7	--	3	7	6-7/8	specify	12	4	6	WS3	8	WS3	10555	10965	11055	1935
	KHGLT7	HGLT7, HGLTV7					12	6	12	WS3	6	WS3	12495	12495	12495	1935
8-3/4	KGLT9	--	3	7	8-7/8	specify	14	4	6	WS3	8	WS3	10555	10965	11055	1935
	KHGLT9	HGLT9					14	6	12	WS3	6	WS3	12495	12495	12495	1935
10-3/4	KHGLT11	--	3	7	10-7/8	specify	16	6	12	WS3	6	WS3	12495	12495	12495	1935

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Allowable Loads are based on 625 psi perpendicular to grain loading.

3) "Specify" denotes the required supported beam height that must be specified at time of ordering, with 7-1/2" being the minimum.

4) MiTek's WS3 structural wood screws are 1/4" dia. x 3" long and are included with the hangers.