

Beam Width (in)	MiTek Stock No.	Ref. No.	Dimensions (in) ²			Fastener Schedule ⁴				Allowable Loads (Lbs.)			
			W	H	D	Header ³		Joist Qty	Type	F _C [^] = 625 psi			Uplift ¹ 160%
						Top Qty	Face Qty			Floor 100%	Roof		
											115%	125%	
3-1/8	KHHB3	--	3-1/4	specify	3	4	6	6	WS3	6480	6480	6480	2215
	KGB3	--			3-1/2	4	10	6	WS3	6480	6480	6480	2215
5-1/8	KHHB5	--	5-1/4	specify	3	4	6	6	WS3	6480	6480	6480	2215
	KGB5	--			3-1/2	4	10	6	WS3	6480	6480	6480	2215
	KHGB5	--			4	4	12	6	WS3	6480	6480	6480	2215
6-3/4	KHHB7	--	6-7/8	specify	3	4	6	6	WS3	6480	6480	6480	2215
	KGB7	--			3-1/2	4	10	6	WS3	6480	6480	6480	2215
	KHGB7	--			4	4	12	6	WS3	6480	6480	6480	2215

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) "Specify" denotes the required supported beam height must be specified at the time of ordering.

3) Supporting header shall be no less than 3" thick.

4) MiTek's WS3 structural wood screws are 1/4" dia. x 3" long and are included with hangers.