

Beam/ Joist Size	MiTek Stock No.	Ref. No.	Steel Gauge	Dimensions (in)					Fastener Schedule <sup>4</sup>				DF/SP Allowable Loads (Lbs.) <sup>2</sup>			
				W	H	D	L	TF	Header		Joist		Floor	Roof		Uplift <sup>1</sup>
									Top Qty	Type	Qty	Type		100%	115%	
<b>Glulam Sizes<sup>3</sup></b>																
2-1/2 glulam	KHW26	--	3/10	2-11/16	specify	4	10	2-1/2	4	NA20D	2	10d x 1-1/2	5295	5295	5295	135
3-1/8 glulam	KHW3	--	3/10	3-1/4	specify	3	10	2-1/2	4	NA20D	2	10d	5535	5535	5535	135
5-1/8 glulam	KHW5	--	3/10	5-1/4	specify	2-1/2	10	2-1/2	4	NA20D	2	10d	5535	5535	5535	135

1) Uplift Loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Refer to the respective Nailer Options chart for hangers installed on wood nailers.

3) **Consult MiTek for additional Glulam sizes.**

4) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, NA20D nails are 0.192" dia. x 2-1/2" long and are included with KHW hangers.