

MiTek Stock No.	Ref. No.	Steel Gauge	Fastener Schedule ^{2,3,5}							Girder Truss	DF/SP Allowable Loads (Lbs.) ¹			S-P-F Allowable Loads (Lbs.) ¹		
			Mounting Condition	Supporting Member				Supported Member ⁴			Floor	Roof		Floor	Roof	
				Top		Face/ Backside						100%	115%		125%	100%
				Qty	Type	Qty	Type	Qty	Type							
MSSH217L/R	--	18	face-max	--	--	16	10d	1	10d x 1-1/2	1 Ply	1755	1770	1770	1140	1155	1165
			top-min	4	10d	6	10d			1 Ply	1735	1735	1735	1140	1155	1165

1) No uplift value with this hanger. Use other hardware or nailing higher on supported member to counteract uplift.

2) One or both straps may be bent over bottom chord of girder with top or backside nailing.

3) Maintain minimum 3/4" edge distance when installing nails.

4) The supported member shall be supported by blocking or other means to prevent rotation.

5) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long.

Note: The 3 lower holes on each strap are for top nailing when strap is bent. These holes are not for face nailing.