

Post Size	MiTek Stock No.	Ref. No.	Steel Gauge	Dimensions (in)					Fastener Schedule ^{2,3}				DF/SP Allowable Loads (Lbs.) ^{1,2}		
				W	H1	H2	L1	L2	Post		Beam		Uplift 160%	F1 160%	F2 160%
									Qty	Type	Qty	Type			
4 x 4	PB44-6TZ	LPC4Z	18	1-1/2	2-1/8	1-1/2	--	3-5/8	8	16d HDG	8	16d HDG	585	1760	1015
	PBES44	LCE4	18	1-1/2	2-3/8	2-3/4	3-1/4	4-3/4	8	16d	8	16d	1765	920	810
	PBS44	AC4	18	1-7/16	2-5/16	2-13/16	3-9/16	6-1/2	12	16d	12	16d	2650	1860	1110
4 x 4 Rough	PBS44R	AC4R	18	1-1/2	2-5/16	2-3/16	4	7	8	16d	8	16d	1765	920	810
6 x 6	PB66-6TZ	LPC6Z	18	1-1/2	2-1/2	3	--	5-9/16	8	16d HDG	8	16d HDG	585	1760	1015
	PBES66	--	18	1-1/2	2-3/8	2-1/8	5-1/2	7	8	16d	8	16d	1670	1190	1235
	PBS66	AC6	18	1-1/4	2-5/16	2-7/8	5-1/2	8	14	16d	12	16d	2015	1865	1300
6 x 6 Rough	PBS66R	AC6R	18	1-1/4	2-5/16	2-3/16	6	8-1/2	10	16d	10	16d	1670	1190	1235

1) Allowable loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) **Allowable Loads and Fastener Schedules for a pair of post caps.**

3) **NAILS:** 16d nails are 0.162" dia. x 3-1/2" long.