

MiTek Stock No.	Ref. No.	Steel Gauge	No. of Plies <sup>6</sup>	Fastener Schedule <sup>5</sup>				DF/SP
				Rafter/Truss		Concrete/Masonry <sup>4</sup>		Allowable Loads (Lbs.)
				Qty	Type <sup>7</sup>	Qty	Screw Anchor <sup>2,3</sup>	Uplift 160% <sup>1</sup>
RFUS	FGTR	10	≥ 2 Ply	12	WS3	4	3/4" x 6"	7100

- 1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.
- 2) Use DeWalt 3/4" x 6" Screw-Bolt™+; or equal, installed in accordance with manufacturer's specifications.
- 3) DeWalt 3/4" x 6" Screw-Bolt™+ are not supplied with RFUS ties.
- 4) Fasteners shall be installed to fully grouted and reinforced masonry units (CMU) type S or better mortar or reinforced concrete (f'c = 2,500 psi at 28 days).
- 5) Fastener shedule is for two straps used together. The straps shall be installed in pairs.
- 6) Truss plies shall be fastened together to act as a single unit.
- 7) MiTek's WS3 structural wood screws are 1/4" dia. x 3" long and are supplied with RFUS connector.