

| MiTek<br>Stock No. | Ref. No. | Steel<br>Gauge | Installation<br>Type <sup>4</sup> | Fastener Schedule <sup>2</sup> |            |                     |            | DF/SP                               |       | S-P-F                               |       |
|--------------------|----------|----------------|-----------------------------------|--------------------------------|------------|---------------------|------------|-------------------------------------|-------|-------------------------------------|-------|
|                    |          |                |                                   | Supporting<br>Member           |            | Supported<br>Member |            | Allowable Loads (Lbs.) <sup>1</sup> |       | Allowable Loads (Lbs.) <sup>1</sup> |       |
|                    |          |                |                                   | Qty                            | Type       | Qty                 | Type       | Download                            | Upift | Download                            | Upift |
|                    |          |                |                                   |                                |            |                     |            | (100/115/125)                       |       | 160%                                |       |
| SNP3               | TJC37    | 16             | Figure 1                          | 6                              | 8d x 1-1/2 | 6                   | 8d x 1-1/2 | 475                                 | 475   | 415                                 | 415   |
|                    |          |                | Figure 2                          | 6                              | 8d x 1-1/2 | 6                   | 8d x 1-1/2 | 335                                 | 335   | 295                                 | 295   |

1) Allowable loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Install specified fasteners from the bend line out from each end. Not all nail holes will be filled.

3) When installing SNP3's back to back, the table loads shall be multiplied by a reduction factor of 0.78.

4) Refer to images for installation type.

5) **NAILS:** 8d x 1-1/2 nails are 0.131" dia. x 1-1/2" long.