

Stud Size	MiTek Stock No.	Ref. No.	Steel Gauge	Dimensions (in)		Fastener Schedule ²		DF/SP Allowable Loads (Lbs.)
				W	H	Qty	Type	Uplift ¹
								160%
4x	SPT4	SP4	20	3-9/16	6-7/8	6	10d x 1-1/2	875
	SPTH4	SPH4	18	3-9/16	8-5/8	12	10d x 1-1/2	2195
	SPTHW4	SPH4R	18	4-1/16	8-3/8	12	10d x 1-1/2	2195
6x	SPT6	SP6	20	5-9/16	7-5/8	6	10d x 1-1/2	875
	SPTH6	SPH6	18	5-9/16	9-3/8	12	10d x 1-1/2	2195
	SPTHW6	SPH6R	18	6-1/16	9-1/8	12	10d x 1-1/2	2195
8x	SPT8	SP8	20	7-5/16	8-1/2	6	10d x 1-1/2	875
	SPTH8	SPH8	18	7-5/16	8-1/2	12	10d x 1-1/2	2195

- 1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.
- 2) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long.