

MiTek Series	Nailer Size	Fastener Schedule ³					DF/ SP		SPF	
		Nailer		Joist			Allowable Loads (Lbs.) ^{2,3}		Allowable Loads (Lbs.) ^{2,3}	
		Top Qty	Face Qty	Type	Qty	Type	Download 100%	Uplift ¹ 160%	Download 100%	Uplift ¹ 160%
TFL	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1270	130	1090	110
	3X	4	2	16d x 2-1/2	2	10d x 1-1/2	1600	130	1260	110
	(2) 2X	4	2	10d	2	10d x 1-1/2	1280	130	1100	110
	4X	4	2	16d	2	10d x 1-1/2	1745	130	1260	110
THO	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1235	230	950	195
	3X	4	2	16d x 2-1/2	2	10d x 1-1/2	1235	230	950	195
	(2) 2X	4	2	16d x 2-1/2	2	10d x 1-1/2	1235	230	950	195
	4X	4	2	16d	2	10d x 1-1/2	1235	230	950	195
THO (Double)	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1455	230	1250	195
	3X	4	2	16d x 2-1/2	2	10d x 1-1/2	2335	230	1815	195
	(2) 2X	4	2	10d	2	10d x 1-1/2	2370	230	1815	195
	4X	4	2	16d	2	10d x 1-1/2	2525	230	1815	195
TFI	2X	4	2	10d x 1-1/2	2	10d x 1-1/2	1985	215	1665	180
	3X	4	6	16d x 2-1/2	2	10d x 1-1/2	2715	215	2075	180
	(2) 2X	4	6	10d	2	10d x 1-1/2	2715	215	2075	180
	4X	4	2	16d	2	10d x 1-1/2	2560	215	2075	180
	4X	4	6	16d	2	10d x 1-1/2	3245	215	2075	180

- 1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.
- 2) Listed loads shall not be increased.
- 3) Values in the table apply to standard top mount hangers without slope, skew or any other specialty options.
- 4) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long, 16d x 2-1/2 nails are 0.162" dia. x 2-1/2" long.