

Rafter Width (in)	MiTek Stock No.	Ref. No.	Steel Gauge	Dimensions (in)		Fastener Schedule ²				DF/SP		S-P-F	
				W	L	Plate		Rafter		Allowable Loads (Lbs.) ¹		Allowable Loads (Lbs.) ¹	
						Qty	Type	Qty	Type	Download	Uplift	Download	Uplift
										(100/115/125)	160%	(100/115/125)	160%
1-1/2	TMP2	VPA2	18	1-9/16	5-9/16	6	10d	4	10d x 1-1/2	1705	250	1705	190
1-3/4	TMP175	VPA25	18	1-13/16	5-9/16	6	10d	4	10d x 1-1/2	1705	250	1705	190
2 or 2-1/8	TMP21	VPA2.06, VPA2.1	18	2-1/8	6-3/8	6	10d	4	10d x 1-1/2	1705	250	1705	190
2-5/16	TMP23	VPA35	18	2-3/8	6-3/8	6	10d	4	10d x 1-1/2	1705	250	1705	190
2-1/2 or 2-5/8	TMP25	VPA3	18	2-11/16	6-3/8	6	10d	4	10d x 1-1/2	1705	250	1705	190
3	TMP31	--	18	3-1/8	7-5/16	6	10d	4	10d x 1-1/2	1705	250	1705	190
3-1/2	TMP4	VPA4	18	3-9/16	7-5/16	6	10d	4	10d x 1-1/2	1705	250	1705	190

1) Allowable Loads are governed by test results; no further increase shall be permitted

2) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long.