

Option	Skewed <sup>1,3</sup>	Sloped Seat <sup>2</sup>	Sloped / Skewed <sup>1,2</sup>	Sloped Top Flange <sup>4</sup>	Top Flange Offset	Saddle
<b>Range</b>	1° to 50°	1° to 45°	See Sloped Seat and Skewed	0° to 30°	May not be skewed	5" minimum saddle
<b>Allowable Loads</b>	KGLS – 6,500-lb Max KHGLS – 7,980-lb Max 50% of uplift load on skews greater than 15°.	KGLS – 6,500-lb Max KHGLS – 9,165-lb Max	KGLS – 5,500-lb Max <b>KHGLS – may not be sloped / skewed.</b>	100% of table load	50% of table load for KGLS. 45% of table load for KHGLS.	100% of table load per side
<b>Ordering</b>	Add <i>SK</i> , angle required, right ( <i>R</i> ) or left ( <i>L</i> ), and square cut ( <i>SQ</i> ) or bevel cut ( <i>BV</i> ) to product number. Ex. KGLS35H115_SK45R_BV	Add <i>SL</i> , slope required, and up ( <i>U</i> ) or down ( <i>D</i> ), to product number. Example: KGLS35H115_SL30D	See Sloped Seat and Skewed. Example: KGLS35H115_SK45R_BV_SL30D	Add <i>SLTF</i> , angle required, and right ( <i>R</i> ) or left ( <i>L</i> ), to product number. Example: KGLS35H115_SLTF30L	Add <i>OS</i> , and right ( <i>R</i> ) or left ( <i>L</i> ), to product number. Example: KGLS35H115_OSL	Add <i>SA</i> , and saddle width required to product number. Example: KGLS35H115_SA=5-1/2"

1) Skewed hangers with skews greater than 15° may have all joist fasteners on outside flange.

2) Sloped or sloped / skewed hangers with slopes greater than 15° may have additional joist nails.

3) Skewed hangers typically require a bevel cut however, a square cut option may be available as a custom when requested.

4) Sloped top flanges with greater than 15° may have additional header nails.