

MiTek Stock No. <sup>1</sup>	Ref. No.	Steel Gauge	Dimensions (in)			Pieces Per Roll	Wall Height (ft)	Install Angle	Fastener Schedule <sup>2</sup>			
			W1	W2	L				Each Plate		Each Stud	
									Qty	Type	Qty	Type
RWB96	WB106C	16	1-1/4	--	9' 6"	15	8'	60°	4	8d	1	8d
RWB114	WB126C	16	1-1/4	--	11' 4-3/8"	12	8'	45°	4	8d	1	8d
RWB143	WB143C	16	1-1/4	--	14' 3"	10	10'	45°	4	8d	1	8d
WBC10	RCWB10	18	7/8	1	9' 5-5/8"	--	8'	60°	2	16d	1	8d
WBC12	RCWB12	18	7/8	1	11' 4-3/8"	--	8'	45°	2	16d	1	8d
WBT10	TWB10	22	1-3/8	--	9' 3"	--	8'	60°	4	8d	1	8d
WBT12	TWB12	22	1-3/8	--	11' 4"	--	8'	45°	4	8d	1	8d
WBT14	RCWB14, TWB14	22	1-3/8	--	14' 2"	--	10'	45°	4	8d	1	8d
WB106	WB106	16	1-1/4	--	9' 5-1/2"	--	8'	60°	3	16d	1	8d
WB126	WB126	16	1-1/4	--	11' 4-1/4"	--	8'	45°	3	16d	1	8d

1) These products substitute for code prescribed 1 x 4 let-in bracing.

2) **NAILS:** 8d nails are 0.131" dia. x 2-1/2" long, 16d nails are 0.162" dia. x 3-1/2" long.