

MiTek Series	Nailer Size	Fastener Schedule ⁴					DF/SP		S-P-F	
		Header			Joist		Allowable Loads (Lbs.) ^{2,3}		Allowable Loads (Lbs.) ^{2,3}	
		Top Qty	Face Qty	Type	Qty	Type	Download 100%	Uplift ¹ 160%	Download 100%	Uplift ¹ 160%
BPH	2X	4	2	10d x 1-1/2	4	10d x 1-1/2	2080	230	1790	200
	3X	4	4	16d x 2-1/2	4	10d x 1-1/2	2360	535	2030	460
	(2) 2X	4	4	10d	4	10d x 1-1/2	2310	535	1985	460
	4X	4	4	16d	4	10d x 1-1/2	2245	535	1930	460
HBPH	2X	6	2	10d x 1-1/2	10	16d	2540	--	2135	--
	3X	6	6	16d x 2-1/2	10	10d	4500	--	3780	--
	(2) 2X	6	8	10d	10	16d	4140	1610	3480	1350
	4X	6	10	16d	10	16d	5745	1610	4825	1350

- 1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.
- 2) Listed loads shall not be increased.
- 3) Values in the table apply to standard top mount hangers without slope, skew or any other specialty options.
- 4) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long, 16d nails are 0.162" dia. x 3-1/2" long, 16d x 2-1/2 nails are 0.162" dia. x 2-1/2" long.