|  |             |                | Dillici | ioiui | 13 (111) | rasteller schedule |              |                | SP Plate '-            |            |            |
|--|-------------|----------------|---------|-------|----------|--------------------|--------------|----------------|------------------------|------------|------------|
|  |             |                |         |       |          |                    |              |                | Allowable Loads (Lbs.) |            |            |
| MiTek<br>Stock No.   | Ref.<br>No. | Steel<br>Gauge | w       | L     | D        | Plate<br>Qty       | Joist<br>Qty | Туре           | F2<br>90%              | F2<br>100% | F2<br>160% |
| LJC-TZ   |             | 18             | 3-3/16  | 8     |          | 6                  | 6            | 8d x 1-1/2 HDG | 515                    | 570        | 670        |
| LJQ35-TZ   |             | 16             | 3-9/16  | 3     | 1-1/2    | 4                  |              | WS15-EXT       | 915                    | 1015       | 1260       |
| 1) LJC-TZ: DF Plate may be substituted for SP Plate with no load reduction. 2) Allowable loads apply to DF/SP dimensional lumber floor joists or EWP I-joists with DF or equivalent bottom chords. |             |                |         |       |          |                    |              |                |                        |            |            |

3) MiTek's WS15-EXT structural wood screws are 1/4" dia. x 1-1/2" long and are included with LJQ35-TZ connector.

Dimoneione (in)

4) **NAILS:** 8d x 1-1/2 HDG nails are 0.131" dia. x 1-1/2" long.

Eastoner Schodule 3.4