

Option	Skewed ^{1,3}	Sloped Seat ²	Sloped / Skewed ^{1,2}	Sloped Top Flange ⁴	Top Flange Offset
Range	1° to 50°	1° to 45°	See Sloped Seat and Skewed	0° to 30°	May not be skewed
Allowable Loads	KGLS – 6,500-lb Max KHGLS – 7,980-lb Max 50% of uplift load on skews greater than 15°.	KGLS – 6,500-lb Max KHGLS – 9,165-lb Max	KGLS – 5,500-lb Max KHGLS – may not be sloped / skewed. 50% of uplift load on skews greater than 15°.	100% of table load	50% of table load for KGLS. 45% of table load for KHGLS.
Ordering	Add <i>SK</i> , angle required, right (<i>R</i>) or left (<i>L</i>), and square cut (<i>SQ</i>) or bevel cut (<i>BI</i>) to product number. Ex. KGLS35H=115_SK45R_BV	Add <i>SL</i> , slope required, and up (<i>U</i>) or down (<i>D</i>), to product number. Example: KGLS35H=115_SL30D	See Sloped Seat and Skewed. Example: KGLS35H=115_SK45R_BV_SL30D	Add <i>SLTF</i> , angle required, and right (<i>R</i>) or left (<i>L</i>), to product number. Example: KGLS35H=115_SLTF30L	Add <i>OS</i> to product number. Example: KGLS35H=115_OS

- 1) Skewed hangers with skews greater than 15° may have all joist fasteners on outside flange.
- 2) Sloped or sloped / skewed hangers with slopes greater than 15° may have additional joist nails.
- 3) Skewed hangers typically require a bevel cut however, a square cut option may be available as a custom when requested.
- 4) Sloped top flanges with greater than 15° may have additional header nails.