

MiTek Series	Nailer Size	Fastener Schedule ⁴					DF/SP Allowable Loads (Lbs.) ³		SPF Allowable Loads (Lbs.) ³	
		Nailer			Joist		Download ² 100%	Uplift ¹ 160%	Download ² 100%	Uplift ¹ 160%
		Top Qty	Face Qty	Type	Qty	Type				
HLBH	2x	3	4	10d x 1-1/2	6	10d x 1-1/2	6115	--	5135	--
	3x	3	6	16d x 2-1/2	6	10d	6825	--	5735	--
	(2) 2x	3	8	10d	6	10d x 1-1/2	4385	--	3685	--
	4X	3	8	NA16D-RS	6	10d x 1-1/2	9600	1115	6900	935
	4X	3	8	NA16D-RS	6	16d	9600	1115	6900	935

1) Uplift loads have been increased 60% for wind or seismic loads; no further increase shall be permitted.

2) Listed download shall not be increased.

3) Values in the table apply to standard top mount hangers without slope, skew or any other specialty options.

4) **NAILS:** 10d x 1-1/2 nails are 0.148" dia. x 1-1/2" long, 10d nails are 0.148" dia. x 3" long,
NA16D-RS nails are 0.148 dia, x 3-1/2" long, 16d nails are 0.162" dia. x 3-1/2" long.