Option	Skewed ^{1,3}	Sloped Seat ^{2,3}	Sloped / Skewed ^{1,2,3}	Inverted Flange
Range	1° to 50°	1° to 45°	See Sloped Seat and Skewed	One or two flanges available on all sizes.
Allowable Loads	100% of table load. 75% of uplift load on skews greater than 15°.	100% of table load	80% of table load. 75% of uplift load on skews greater than 15°.	100% of table load. 65% of table load when nailing into the support members end grain.
Ordering	Add <i>SK</i> , angle required, right <i>(R)</i> or left <i>(L)</i> , and square cut <i>(SQ)</i> or bevel cut <i>(BV)</i> to product number. Example: THF23118-2_SK45R_BV	Add <i>SL,</i> slope required, and up <i>(U)</i> or down <i>(D),</i> to product number. Example: THF23118-2_SL30D	See Sloped Seat and Skewed Example: THF23118-2_SK45R_SL30D_BV	Add <i>IF,</i> to product number. Example: THF23118-2_IF
 Skewed hangers with skews greater than 15° may have all joist nailing on outside flange. Sloped or sloped / skewed hangers with slopes greater than 15° may have additional joist nails. For skewed hangers, the required cut type (square or bevel) of joist member may vary based on skew angle and width of hanger. Some square cut hangers will require custom pricing due to welded back plate. 				